

HiStone

Luna-X PoS System



HiStone

Luna-X HK560 POS System (Windows & Linux)

HiStone's Luna-X PoS System is a stylish, compact, and versatile point of sale system with an innovative adjustable hinge design that allows for flexible configuration that can be used for retail, hospitality, and various other applications. The cable management integrated into the stand ensures a clutter-free countertop. It can also be wall-mounted for added versatility, making this ideal for varied business requirements.

The Luna-X delivers everything you need in a reliable point of sale system with an optional thermal printer seated on the stand beneath the screen, 2nd customer-facing display for a more engaging checkout experience, and a sleek design to improve user experience.



With its flexibility and adaptability, it's able to serve as both a traditional point of sale system as well as a self-service terminal for kiosks and unattended locations.

Features

- ❑ Semi-integrated PoS with 15.6" True flat capacitive touchscreen
- ❑ Fanless design for silent operation
- ❑ Space-saving compact footprint
- ❑ Smart hinge design for screen rotation and flexibility
- ❑ Optional 10.1" LCD or VFD customer-facing display
- ❑ Optional integrated biometric fingerprint reader
- ❑ Optional operator-facing 2D barcode scanner
- ❑ Optional integrated MSR (3-tracks USB)
- ❑ Optional 80mm thermal printer seated neatly on the stand beneath the main display
- ❑ Wall-mount capabilities

Customizable Options

Choose from a range of peripherals to suit your retail or hospitality environment.



15.6" LED Screen with Smart Hinge Design and stand extender for Screen Rotation (Self-Ordering Kiosk)

Optional 80mm Thermal Printer (with screen in high position)



Integrated HID Biometric Fingerprint Reader

Integrated MSR (3-track USB)

Customer-facing 2x20 Characters VFD



Customer-facing 10.1" LCD



Biometric Fingerprint Reader on external cradle.

Handheld & Presentation Barcode Scanners



308mm or 410mm Wide Cash Drawer

Handheld Barcode Scanner on external cradle



| MODEL | | HK560E | HK560M |
|----------------------|----------------|---|---|
| Processor | | Intel® Bay Trail J1900, Quad-core 2.0GHz up to 2.42GHz | Intel® Core™ Skylake-U, 6th Generation High-Performance CPU i3-6100U SOC 2.3GHz |
| Operating System | | Windows 10 & Linux | Windows 10 & Linux |
| Memory | | SO-DIMM DDR3L 1066/1333MHz 4GB up to 8GB | SO-DIMM DDR4 2133MHz 4GB up to 16GB |
| Storage | | SATA SSD 120GB up to 240GB | SATA SSD 120GB up to 240GB |
| Display Panel | | 15.6" LED widescreen Standard resolution: 1920 x 1080 | 15.6" LED widescreen Standard resolution: 1920 x 1080 |
| Touch Screen | | True flat capacitive touch screen | True flat capacitive touch screen |
| Power Supply | | 24V 60W (Standard) 24V 120W (Optional) | 24V 60W (Standard) 24V 120W (Optional) |
| Speaker | | 1* 2W Speaker | 1* 2W Speaker |
| I/O Ports | USB | 5* 2.0, 1* 24V Powered, 1* 3.0 | 4* 2.0, 1* 24V Powered, 2* 3.0 |
| | Serial | 3* RJ48 | 3* RJ48 |
| | LAN | 1* RJ45 100M/1000M Gigabit | 1* RJ45 100M/1000M Gigabit |
| | Cash Drawer | 1* 24V RJ11 | 1* 24V RJ11 |
| | Audio | 1* 3.5mm | 1* 3.5mm |
| | HDMI | Not supported | 1* HDMI |
| Optional Peripherals | Camera | Normal security camera | Normal security camera |
| | | Face ID camera | Face ID camera |
| | Wi-Fi® | Single-band 802.11a/b/g/n 2.4GHz | Dual-band 802.11a/b/g/n/ac 2.4GHz/5GHz |
| | | Dual-band 802.11a/b/g/n/ac 2.4GHz/5GHz | |
| | Bluetooth | Not supported | Not supported |
| | Second Display | 15.6" Touch / Non-touch Resolution: 1920 x 1080 | 15.6" Touch / Non-touch Resolution: 1920 x 1080 |
| | | 10.1" Touch / Non-touch Resolution: 1280 x 800 | 10.1" Touch / Non-touch Resolution: 1280 x 800 |
| | | 2x20 Characters VFD | 2x20 Characters VFD |
| | Printer | Separate 80mm thermal printer | Separate 80mm thermal printer |
| | MSR | 3 tracks MSR | 3 tracks MSR |

| MODEL | | HK560E | HK560M |
|-------------------------|--------------------|--|--|
| Optional Peripherals | RFID | MSR & RFID (Supports MIFARE one & MIFARE CPU card) | MSR & RFID (Supports MIFARE one & MIFARE CPU card) |
| | Scanner | Handheld or Presentation | Handheld or Presentation |
| | FPR | 1* Fingerprint reader | 1* Fingerprint reader |
| | Stand | Normal desktop stand | Normal desktop stand |
| | | Heightened desktop stand for vertical screen rotation for self ordering kiosk option | Heightened desktop stand for vertical screen rotation for self ordering kiosk option |
| Wall Mount | Wall mount bracket | Wall mount bracket | |
| Dimensions (WxDxH) | | 405 x 210 x 330 mm (single display) | 405 x 210 x 330 mm (single display) |
| | | 405 x 250 x 370 mm (dual display) | 405 x 250 x 370 mm (dual display) |
| Weight | | 6kg (Standard but varies depending on configuration) | 6kg (Standard but varies depending on configuration) |
| Tilt Adjustment | | 0° - 45° (Vertical) | 0° - 45° (Vertical) |
| Environment | Operating | 0°C - 45°C / 10%-90% RH non-condensing | 0°C - 45°C / 10%-90% RH non-condensing |
| | Storage | -10°C - 70°C / 10%-90% RH non-condensing | -10°C - 70°C / 10%-90% RH non-condensing |
| EMC and Safety | | FCC / CE / RoHS | FCC / CE / RoHS |
| Colour | | Black or White | Black or White |

All products specifications are subject to change without notice.